



**SPECIFICATION**

- Voltage rating: 250V AC, DC
- Current Rating: 3A, AC, DC
- Withstand voltage: 800V AC/minute
- Contact resistance: 20mΩmax
- Insulation resistance: 1000MΩmin
- Temperature range: -25°C ~ +85°C

**HOUSING**

- Material: PA66 UL94V-0



**DIMENSION:**

CIRCUITS	DIM. A	DIM. B	DIM. C	DIM. D
02	6.10	4.34	2.00	2.6
03	8.10	6.34	4.00	3.45
04	10.10	8.34	6.00	4.5
05	12.10	10.34	8.00	4.5
06	14.10	12.34	10.00	
07	16.10	14.34	12.00	
08	18.10	16.34	14.00	
09	20.10	18.34	16.00	11.1
10	22.10	20.34	18.00	
11	24.10	22.34	20.00	
12	26.10	24.34	22.00	
13	28.10	26.34	24.00	
14	30.10	28.34	26.00	
15	32.10	30.34	28.00	
16	34.10	32.34	30.00	

GENERAL TOLERANCE	
0	±0.30
.0	±0.20
.00	±0.15
.000	±0.10

版本	变更内容	日期		单位	mm	比例	1:1	日期	20131210
----	------	----	--	----	----	----	-----	----	----------

核准	审核	绘图	品名	PA2.0mm HSG		
		bolly	料号	JVT2032HN0-XXL		
			图名	031	版本	A

A

B

C

D

E

F

G

H

1

2

3

4

1

2

3

4

A

B

C

D

E

F

G

H

乔业电子有限公司

CHYAO YEE CONNECTORS CO.,L TD